


- Отоплителни и тръбни системи
- Стоманени тръби и елементи



Редукция тип C12

Приложение

- Климатични системи затворен тип



	Размери				
	$\varnothing d - \varnothing d1$ [mm]	L [mm]	A [mm]	Z [mm]	W [g]
C12CB	15.0 - 12.0	51	18	33	26
C12DB	18.0 - 12.0	53	18	35	32
C12DC	18.0 - 15.0	55	21	34	36
C12EB	22.0 - 12.0	60	18	42	39
C12EC	22.0 - 15.0	60	21	39	42
C12ED	22.0 - 18.0	57	21	36	44
C12FB	28.0 - 12.0	75	18	57	55
C12FC	28.0 - 15.0	81	21	60	62
C12FD	28.0 - 18.0	84	21	63	68
C12FE	28.0 - 22.0	70	23	47	67
C12GC	35.0 - 15.0	84	21	63	84
C12GD	35.0 - 18.0	87	21	66	90
C12GE	35.0 - 22.0	76	23	53	95
C12GF	35.0 - 28.0	74	26	48	87
C12HD	42.0 - 18.0	98	21	77	180
C12HE	42.0 - 22.0	87	23	64	177
C12HF	42.0 - 28.0	100	24	76	128
C12HG	42.0 - 35.0	78	26	52	115
C12JD	54.0 - 18.0	108	21	87	190
C12JE	54.0 - 22.0	110	22	88	185
C12JF	54.0 - 28.0	100	24	76	185
C12JG	54.0 - 35.0	129	27	102	206
C12JH	54.0 - 42.0	108	32	76	189
C12KH	76.1 - 42.0	151	32	119	425
C12KJ	76.1 - 54.0	145	37	108	454
C12LJ	88.9 - 54.0	157	37	120	591
C12LK	88.9 - 76.1	157	52	105	660
C12MJ	108.0 - 54.0	204	37	167	880
C12MK	108.0 - 76.1	196	52	144	948
C12ML	108.0 - 88.9	192	59	133	962

Забележки

- $\varnothing d - \varnothing d1$ = диаметри
- W = тегло